

B1

"This application is a continuation application claiming priority under 35 U.S.C. § 120 from Application Serial No. 09/328,329 which issued into U. S. Patent No. 6,377,847 on April 23, 2002, that is a continuation-in-part of Application No. 08/533,979 filed September 26, 1995, now abandoned, which is a continuation-in-part of Application No. 08/129,222 filed September 30, 1993, now abandoned."

*SJ
C1*

In the Claims:

B2

Claims 22-69 are pending. Please amend the following claims.

29. (Once Amended) The iontophoretic drug delivery device of claim 28, wherein the concentration of glycerin is up to 10 wt. %, the concentration of sodium metabisulfite is up to 0.05 wt. %, the concentration of EDTA is up to 0.01 wt. %.

B3

31. (Once Amended) The iontophoretic drug delivery device of claim 24, wherein the concentration of epinephrine, as measured in weight % of the total weight of the reservoir, is about 0.1 wt. % and the concentration of lidocaine is about 10 wt. %.

B4

34. (Once Amended) The iontophoretic drug delivery device of claim 33, wherein the one to three return electrodes have a total surface area between 1 to 5 cm² and wherein the working electrode has a surface area between 2 to 10 cm².

B5
57. (Once Amended) The iontophoretic drug delivery device of claim 56,
wherein the lidocaine is present up to 10 wt. % based on the total weight of the
reservoir.

B6
59. (Once Amended) The iontophoretic drug delivery device of claim 58,
wherein the concentration of glycerin is up to 10 wt. %, the concentration of
sodium metabisulfite is up to 0.05 wt. %, the concentration of EDTA is up to 0.01
wt. %, all based on the total weight of the reservoir.

60. (Once Amended) The iontophoretic drug delivery device of claim 54,
wherein the concentration of epinephrine, as measured in weight % of the total
weight of the reservoir, is about 0.1 wt. % and the concentration of lidocaine is
about 10 wt. %, all based on the total weight of the reservoir.

B7
63. (Once Amended) The iontophoretic drug delivery device of claim 62,
wherein the return electrodes have a total surface area from 1 to 5 cm² and
wherein the working electrode has a surface area from 2 to 10 cm².